



FLIGHT :	#VOL :	ATIS :
-----------------	---------------	---------------

QNH	FRA / FLEVEL	ZFW	FUEL / MIN/DIV	CG / TRIM	PAX	T/O WEIGHT	RATED OR REDUCED	TEMP ACTUAL	MAX TEMP MT	RWY	FLAPS 2 5 10	BLEED ON OFF	ENG ANTI ICE	EPR N1

V1 (BLANC)	VR (BLANC)	V2 (ORANGE)	V TARGET (V2+15) (BLANC)	VZF -117 = 210 +117 = 220 BLANC

<h2 style="color: green;">Takeoff Briefing</h2>	Runway condition vs Winds	0	1	2	2.5	3	4	5	6 _{DRY}		
	Weight Restriction										
	Takeoff distance										
	Expected taxi, hotspots										
	NOTAMS & MEL (AVION)										
<h2 style="color: red;">Threats and Error Management</h2>	Weather & T/O Alternate										
	Fuel for Holding and diversion	(HOLD 1000 lbs / tour) (3000 lbs / 30 minutes)									
	Temperature correction										
	TLR Procedure										

NOTES :

FLAP POSITION	UP TO 117,000 LBS (53,070 KGS)	ABOVE 117,000 LBS (53,070 KGS) UP TO 138,500 LBS (62,823 KGS)	ABOVE 138,500 LBS (62,823 KGS)
FLAPS UP	210	220	230
FLAPS 1	190	200	210
FLAPS 5	170	190	200
FLAPS 10	160	180	190
FLAPS 15	150	160	170
FLAPS 25	140	150	160



BUILD BUG BRIEF

1 STAR	2 APR PLATE	3 STD CALL	4 MISS APR BRIEF	5 PERF	6 LDG BRIEF	7 THREATS

POIDS (LBS)	BLEED ON OFF	FLAPS 15 30 40	VREF DOUBLE BLANC	V TARGET ORANGE	VREF + 15 BLANC	VZF BLANC	MINIMUM ALTITUDE
		30					
		15					

Vref + ½ Headwind
+ Gust (+5min/+20max)

-117 = 210 | +117 = 220

<h2 style="color: blue;">Landing Briefing</h2>	Runway condition vs Winds	0	1	2	2.5	3	4	5	6 _{DRY}		
	Weight Restriction										
	Landing distance										
	Expected exit, taxi, hotspots										
<h2 style="color: red;">Threats and Error Management</h2>	NOTAMS & MEL										
	Weather & T/O Alternate										
	Fuel for Holding and diversion	(HOLD 1000 lbs / tour) (3000 lbs / 30 minutes)									
	Temperature correction										
	TLR Procedure										

ATIS :

NOTES :

Flap Extension Schedule

Current Flap Position	At Speed (knots) a* / b* / c*	Select Flaps	Command Speed for Selected Flaps a* / b* / c*
Up	210 - 220 - 230	1	190 - 200 - 210
1	190 - 200 - 210	5	180 - 190 - 200
5	180 - 190 - 200	10	170 - 180 - 190
10	170 - 180 - 190	15	150 - 160 - 170
15	150 - 160 - 170	25	140 - 150 - 160
25	140 - 150 - 160	30 or 40	(VREF30 or VREF40) + wind additives

a* = At and below 117,000 lbs/53,070 kgs
 b* = Above 117,000 lbs/53,070 kgs and up to 138,500 lbs/62,823 kgs
 c* = Above 138,500 lbs/62,823 kgs